

TAP BITS WITH HEXAGONAL DRIVE 1/4" - SET 4/7

ITEM: 844/7

Set of tap bits for metric threads on metal and quick-change magnetic bit holder. Sturdy tool case in impact-resistant plastic material. Taps with 1/4" hexagonal shank for bit holders DIN ISO 1173-D 6,3. Bit holders for screwdrivers with connection DIN ISO 1173-F 6,3.

Composition:

844 Taps M3 - M4 - M5 - M6 - M8 - M10

888/4/1 K Rapidaptor magnetic quick-change bit holder

Tech. Code	Pieces
E750707	7

COMBINED THREADED DRILLING TAP BITS WITH HEXAGONAL DRIVE 1/4"

ITEM: 847 HSS

Combined threaded-drilling tap bits made of high quality HSS steel, for drilling, threading and countersinking with a single tool. The elasticity of the material guarantees a long tool life.

Tap bits with 1/4" hexagonal shank for bit holders DIN ISO 1173-D 6,3.

Tech. Code	M	I mm	L mm		Tech. Code	M	I mm	L mm	
E750803	3	24	36	1	E750806	6	32	44	1
E750804	4	27	39		E750808	8	39	51	
E750805	5	29	41		E750810	10	47	59	

COMBINED THREADED-DRILLING TAP BITS WITH HEXAGONAL DRIVE 1/4" - SET 847/7

ITEM: 847/7

Set of combined threaded-drilling tap bits and quick-change magnetic bit holder. Sturdy tool case in impact-resistant plastic material. Bit taps with 1/4" hexagonal shank for bit holders DIN ISO 1173-D 6,3. Bit holder for screwdrivers with connection DIN ISO 1173-F 6,3.

Composition:

847 Combined taps M3 - M4 - M5 - M6 - M8 - M10

888/4/1 K Rapidaptor magnetic quick-change bit holder

Tech. Code	Pieces
E750907	7

COUNTERSINKS 90° Z3 WITH HEXAGONAL DRIVE 1/4"

ITEM: 846/3

Countersinks DIN 335C 90° with 3 high quality HSS steel cutting edges for countersinking on metal. The elasticity of the material guarantees a long tool life. Countersinks with 1/4" hexagonal shank for bit holders DIN ISO 1173-D 6,3.

Tech. Code	D mm	I mm	L mm		Tech. Code	D mm	I mm	L mm	
E751006	6,3	11	31	1	E751012	12,4	15	35	1
E751008	8,3				E751016	16,5	20	40	
E751010	10,4	14	34		E751020	20,5	21	41	

COUNTERSINKS 90° Z3 WITH HEXAGONAL DRIVE 1/4" - SET 846/8

ITEM: 846/8

Set of countersinks DIN 335C 90° with 3 HSS cutting edges, quick-change magnetic bit holder and a Kraftform Plus Rapidaptor bit holder handle. Countersinks with 1/4" hexagonal shank for bit holders DIN ISO 1173-D 6,3 Bit holder for screwdrivers with connection DIN ISO 1173-F 6,3. Handle with connection DIN ISO 1173-C 6,3 - ISO 1173-E 6,3.

Composition:

846/3 HSS Countersinks Ø 6,3 - 8,3 - 10,4 - 12,4 - 16,5 - 20,5 mm

888/4/1 K Rapidaptor magnetic quick-change bit holder

816 R Kraftform Plus Rapidaptor magnetic bit holder handle

Tech. Code	Pieces
E751108	7