

ELECTRIC CHAIN HOISTS ATEX - ZONA 22

ITEM: M0013

High quality electric chain hoist, thanks to the high FEM class. Suitable for use in hazardous environments classified Atex Zone 22 dust. ATEX coding II 3D Ex tc IIIA T130 ° C Db

Features:

- Electromechanical drive
- Chain with safety factor "8"
- Die-cast aluminum structure and tempered steel wheel
- Polygonal motor shaft coupling with trefoil
- Low voltage commands (42V)
- Adjustment-free brake and emergency overload included
- Three-phase feed 380V 50 Hz

Advantages:

- Suitable for a large number of operations
- Suitable for outdoor use, IP65 protection
- Usable between -15 ° and +50 ° C

Equipment:

- Chain bucket
- Instruction manual of use and maintenance



ON-LINE
MANUAL

ATEX^{Ex}

Tech. Code		Load capacity kg	Model	Class FEM (ISO)	Speed m/min	NR. CHAIN FALLS N°	HOOK RUN m	Power kW	INTENSITY A	Weight kg
M00131251NF		125	GPD250/1NF	4m (M7)	8/2	1	3	0,72/0,18	2,8/1,7	24
M00132001NF		200		3m (M6)						
M00132501NF		250		2m (M5)						
M00132502NF			GPD250/2NF	8/2	1	26				
M00132501NF2			GPD500/1NF	4/1	2	25				
M00135002NF		500	GPD250/2NF	8/2	1	26				
M00135001NF			GPD500/1NF	4/1	2	28				
M00135002NF2			GPD500/2NF	8/2	1	62				
M001310002NF		1000	GPD1000/1NF	4/1	2	66				
M001310001NF			GPD1000/2NF	8/2	1	93				
M001316002NF			1600	GPD1600/1NF	4/1	2		66		
M001316001NF		GPD1000/2NF		8/2	1	100				
M001320002NF		2000		GPD2500/1NF	4/1	2		66		
M001320001NF			GPD1000/2NF	8/2	1	93				
M001325002NF			2500	GPD1600/1NF	4/1	2		66		
M001325001NF		GPD1600/1NF		8/2	1	93				
M001325001NF2		GPD2500/1NF		4/1	2	100				
M001332002NF		3200	GPD1600/2NF	6,4/1,6	1	2		3,7/0,93	9,7/5,5	102
M001332001BF			GPD2500/1BF	4/1						
M001340002NF			GPD1600/2NF	4/1						
M001340002NF2		4000	GPD2500/2NF	4/1	2	117				
M001350002NF			5000	2m (M5)						
M001363002BF			6300	GPD2500/2BF						1Am (M4)

Related products

CUT RESISTANCE GLOVES COATED IN POLYURETHAN

Tech. Code	EU size
K234007	7
K234008	8
K234009	9
K234010	10

Product available in index K