

ELECTRIC TROLLEY FOR BEAMS

ITEM: M0165

Electric trolley for beams.

Features:

- For GP hoists with ring suspension
- Four steel ball bearing mounted wheels, two motorized and two idler
- Cast iron casing
- Equipped with anti-impact and anti-derailment safety system

Advantages:

- Suitable for a high number of operations due to high FEM class
- Can be used between -15° and +50°

Supplied with:

- Pin for coupling to hoist
- Use and maintenance manual

ON-LINE
MANUAL



Tech. Code	Capacity kg	Model	Speed m/min	Power kW	Intensity A	Width Z mm	Suitable for hoist	Weight kg
M01651250/1	up to 1250	GMF1250	12/4	0.15 / 0.45	1.0 / 1.2	70 - 119	GP250/GP500	30
M01651250/2						120 - 240		
M01652500/1	up to 2500	GMF2500				88 - 300	GP1000	38
M01654000/1	fino a 4000	GMF4000				91 - 300	GP1600 / GP2500	55
M01655000/1	up to 5000	GMF5000						63
M01656300/1	up to 6300	GMF6300						78

ELECTRIC TROLLEY FOR BEAMS - ATEX

ITEM: M0175

Electric trolley for beams suitable for use in hazardous areas classified ATEX.

Zone 22 dust code: II 3D Ex Tc IIIA T 130 ° C Db

Zone 2 gas coding: II 3G Ex Pz IIA T3 Db

Features:

- For GIS GP pranchi with suspension and ring
- Four steel wheels mounted on ball bearings, two motorized and two idle
- Cast iron shells
- Equipped with shockproof and anti-fall protection for derailment

Advantages:

- Suitable for a large number of operations, thanks to the high FEM class
- Usable between -15 ° and + 50 ° C

Equipment:

- Pin for coupling with the hoist
- Use and maintenance manual

ON-LINE
MANUAL



Tech. Code		Load capacity kg	Model	Zona	Speed m/min	Power kW	INTENSITY A	Ala Z mm	Suitable for hoists	Weight kg
M01751250/1P		fino a 1250	GMFD1250	22	12/4	0.15 / 0,045	0,65 / 0,75	70 - 119	GP250 - GP500	30
M01751250/2P								120 - 240		
M01752500/1P		fino a 2500	GMFD2500					88 - 300	GP1000	38
M01754000/1P		fino a 4000	GMFD4000					91 - 300	GP1600 - GP2500	55
M01755000/1P		fino a 5000	GMFD5000							63
M01756300/1P		fino a 6300	GMFD6300							78
M01751250/1G		fino a 1250	GMFG1250	2				70 - 119	GP250 - GP500	30
M01751250/2G								120 - 240		
M01752500/1G		fino a 2500	GMFG2500					88 - 300	GP1000	38
M01754000/1G		fino a 4000	GMFG4000					91 - 300	GP1600 - GP2500	55
M01755000/1G		fino a 5000	GMFG5000							63
M01756300/1G		fino a 6300	GMFG6300							78