

2-HANDLING 3 BALLASTED REVOLVING CRANES 360 ° WITH MANUAL EXTENSION

ITEM: M9410

Features:

- Lifting with double delivery manual pump that allows fast lifting
- High-capacity pivoting wheels with high smoothness with bumper supports and parking brakes
- 360 ° rotatable
- Extendable lifting arm in 4 different positions
- Load descent adjusted by means of a handwheel incorporated in the pump

Advantages:

- Suitable for front loading directly into the mouth of work center load
- Reduces operator effort thanks to the hydraulic cylinder of the larger pump
- Extremely versatile thanks to the small size that the allow you to reach even narrow spaces

Equipment:

- Use and maintenance manual
- Ballast equipped with handles
- Additional extension arm on request

Tech. Code		M9410200	M9410500	M9431PRL
Load capacity	kg	200 - 170 - 150 - 130	500 - 420 - 370 - 320	Extension
Cantilever	mm	365 - 500 - 635 - 770		-
A max	mm	2500		-
Capacity with extension	mm	92 - 85 - 78 - 71	220 - 200 - 180 - 160	-
Cantilever with extension	mm	865 - 1000 - 1135 - 1270		-
A max with extension	mm	2850		-
Weight with ballast	kg	400	600	-

ON-LINE
MANUAL

2-HANDLING 3 BALLASTED REVOLVING CRANES 360° WITH MANUAL EXTENSION

ITEM: M9415

Features:

- Electric lifting by means of a push-button panel that maneuvers the up and down of the arm
- High-capacity pivoting wheels with high smoothness with bumper supports and parking brakes
- 360 ° rotatable
- Extendable lifting arm in 4 different positions
- Load descent adjusted by means of a handwheel incorporated in the pump

Advantages:

- Suitable for front loading directly into the mouth of work center load
- Extremely versatile thanks to the small size that the allow you to reach even narrow spaces

Equipment:

- Use and maintenance manual
- 12V battery and high frequency battery charger
- Ballast equipped with handles
- Additional extension arm on request

Tech. Code		M9415200	M9415500	M9430BAT	M9431PRL
Load capacity	kg	200 - 170 - 150 - 130	500 - 420 - 370 - 320	Battery	Extension
Cantilever	mm	365 - 500 - 635 - 770		-	-
A max	mm	2500		-	-
Capacity with extension	kg	92 - 85 - 78 - 71	220 - 200 - 180 - 160	-	-
Cantilever with extension	mm	865 - 1000 - 1135 - 1270		-	-
A max with extension	mm	2850		-	-
Weight with ballast	kg	440	640	-	-

M9415200 Equipment not subject to periodic visits by certification bodies for certification of use and maintenance status.

ON-LINE
MANUAL