

## 2-HANDLING 3 ELECTRIC BALLASTED CANTILEVER CRANES WITH PROGRESSIVE LIFTING AND MANUAL EXTENSION

### ITEM: M9445

#### Features:

- Electric lifting by means of a proportional joystick that maneuvers the lifting and lowering of the arm
- Equipped with two fixed wheels and two fully loaded steering wheels connected to the guide rudder, to allow extreme maneuverability even when fully loaded
- Extendable lifting arm in 4 different positions
- Load descent adjusted by means of a handwheel incorporated in the pump

#### Advantages: -

- Suitable for front loading directly into the mouth of work center load
- Extremely versatile thanks to the small size that the allow you to reach even narrow spaces

#### Equipment:

- Use and maintenance manual
- 12V battery and high frequency battery charger
- Ballast equipped with handles
- Additional extension arm on request

Tech. Code		M94451000	M9430BAT	M9455PRL
Load capacity	kg	1000 - 835 - 670 - 500	Battery	Extension
Cantilever	mm	650 - 850 - 1050 - 1250	-	-
A max	mm	2640	-	-
Capacity with extension	kg	450 - 390 - 325 - 275	-	-
Cantilever with extension	mm	1400 - 1600 - 1800 - 2000	-	-
A max with extension	mm	3030	-	-
Weight with ballast	kg	1190	-	-

ON-LINE  
MANUAL

## 2-HANDLING 3 CANTILEVER CRANE WITH LIFTING AND ELECTRIC EXTENSION

### ITEM: M9450

#### Features:

- Electric lifting and extension through joystick control that maneuvers the ascent, the descent and extension of the arm
- Equipped with two fixed wheels and two fully loaded steering wheels connected to the guide rudder to allow extreme maneuverability even when fully loaded
- Continuously extendable lifting arm over the entire length
- Load descent adjusted by means of a handwheel incorporated in the pump

#### Advantages:

- Suitable for front loading directly into the mouth of work center load
- Extremely versatile thanks to the small size that the allow you to reach even narrow spaces

#### Equipment:

- Use and maintenance manual
- 12V battery and high frequency battery charger
- Ballast equipped with handles
- Additional extension arm on request

Tech. Code		M94501000	M9430BAT	M9455PRL
Load capacity	kg	1000 - 500	Battery	Extension
Cantilever	mm	650 - 1250	-	-
A max	mm	2670	-	-
Capacity with extension	mm	200	-	-
Cantilever with extension	mm	1400 - 2000	-	-
A max with extension	mm	3120	-	-
Weight with ballast	kg	1195	-	-

ON-LINE  
MANUAL