

ALPAV EXTERNAL THREADS MICROMETERS



ITEM: BB105

Used for 60° thread setting (metric and UN) or 55°(Whitworth standards), average diameter measures. 0.01mm resolution - Graduated thimble with sensitive friction, locking screw system, provided with 60° metric anvils and setting stand. Non- rotating spindle.

Tech. Code	Measuring range mm	Anvils 60° Included
D1345025	0 ÷ 25	1 - 2 - 3 - 4 - 5
D13452550	25 ÷ 50	2 - 3 - 4 - 5 - 6
D13455075	50 ÷ 75	3 - 4 - 5 - 6
D134575100	75 ÷ 100	
D1345100125	100 ÷ 125	4 - 5 - 6
D1345125150	125 ÷ 150	
D1345150175	150 ÷ 175	
D1345175200	175 ÷ 200	

Anvils 60°		
n°	Metric thread Pitch / mm	Thread UN - UNC - UNF Pitch / inch
1	0,4 - 0,5	64 - 48
2	0,6 - 0,8	44 - 28
3	1,0 - 1,75	24 - 14
4	2,0 - 3,0	13 - 9
5	3,5 - 5,0	8 - 5
6	5,5 - 7,0	4,5 - 3,5

ALPAV DIGITAL DISK MICROMETERS FOR GEARS IP65



ITEM: BA050

0.001mm resolution - Digital Micrometer with disk contact surfaces and 8mm-diam non rotating spindle. Zero-setting function, ABS/INC, IP65 protection against particles, ON/OFF button, mm/inch conversion.

Tech. Code	Measuring range mm	D Ø mm	A mm	B mm	C mm	S mm
D1365025	0 ÷ 25	20	59.5	8	32	0.7
D13652550	25 ÷ 50		85.5		44.5	
D13655075	50 ÷ 75		109.5		57	
D136575100	75 ÷ 100		134.5	10	70	

Tech. Code	Model
D99051,5V	Battery 1.5V SR44

ALPAV DISK MICROMETERS FOR GEARS



ITEM: BB075

0.01mm resolution - with disk measuring faces, lapped measuring surfaces, lock lever.

Tech. Code	Measuring range mm	Backing pad Ø mm	A mm	B mm	C mm	S mm
D1370025	0 ÷ 25	20	32	8	32	0.7
D13702550	25 ÷ 50		57		44,5	
D13705075	50 ÷ 75		85		57	
D137075100	75 ÷ 100		107	10	70	
D1370100125	100 ÷ 125	30	133		82	0,9
D1370125150	125 ÷ 150		158		94,54	
D1370150175	150 ÷ 175		183		107	
D1370175200	175 ÷ 200		209		120	

Exacto

Exacto

Exacto

