

## ALPA\ INSIDE MICROMETERS WITH MODULARS EXTENSION RODS



ITEM: BB250

0.01 mm resolution - modular inside micrometers including an inside micrometric head and several extension rods. Micrometric head features a hardened steel contact surface.  
Supplied in a wooden box package.

| Tech. Code    | Measurement range<br>mm | Micron. head<br>mm | Ø<br>mm | Extensions<br>mm                                           |
|---------------|-------------------------|--------------------|---------|------------------------------------------------------------|
| D137550300    | 50 + 300                | 50 + 65            | 16      | 13 - 25 - 50 - 100                                         |
| D137550600    | 50 + 600                |                    |         | 13 - 25 - 50<br>100 - 150 - 200                            |
| D1375501000   | 50 + 1000               |                    |         | 13 - 25 - 50 - 100 (2pcs)<br>150 - 200 - 300               |
| D1375501500   | 50 + 1500               |                    |         | 13 - 25 - 50 - 100 (2pcs)<br>150 - 200 (2pcs) - 300 (2pcs) |
| D13751502000  | 150 + 2000              | 150 + 175          | 23      | 25 - 50 (2pcs) - 100 - 150<br>200 (2pcs) - 400 (3pcs)      |
| D137510003000 | 1000 + 3000             |                    | 28      | 50 - 100 (2pcs) - 200 (2pcs)<br>500 - 1000 (2pcs)          |

## ALPA\ EXTERNAL THREADS DIGITAL MICROMETERS IP65



ITEM: BA080

0.001 mm resolution - digital micrometer with IP65 protection against particles, supplied with 60° metric anvils.

| Tech. Code  |  | Measuring range<br>mm | Anvils 60°<br>Included | Accuracy<br>mm |
|-------------|--|-----------------------|------------------------|----------------|
| D1340025    |  | 0 ÷ 25                | 1 - 2 - 3 - 4 - 5      | ± 0.002        |
| D13402550   |  | 25 ÷ 50               | 2 - 3 - 4 - 5 - 6      |                |
| D13405075   |  | 50 ÷ 75               | 3 - 4 - 5 - 6          |                |
| D134075100  |  | 75 ÷ 100              |                        |                |
| D1340100125 |  | 100 ÷ 125             | 4 - 5 - 6              | ± 0.003        |
| D1340125150 |  | 125 ÷ 150             |                        |                |

ON-LINE  
MANUAL

| Tech. Code | Model             |
|------------|-------------------|
| D99051,5V  | Battery 1.5V SR44 |

| Anvils 60° |                             |                                       |
|------------|-----------------------------|---------------------------------------|
| n°         | Metric thread<br>Pitch / mm | Thread UN - UNC - UNF<br>Pitch / inch |
| 1          | 0,4 - 0,5                   | 64 - 48                               |
| 2          | 0,6 - 0,9                   | 44 - 28                               |
| 3          | 1,0 - 1,75                  | 24 - 14                               |
| 4          | 2,0 - 3,0                   | 13 - 9                                |
| 5          | 3,5 - 5,0                   | 8 - 5                                 |
| 6          | 5,5 - 7,0                   | 4,5 - 3,5                             |

## ALPA\ SPARE ANVILS SET



ITEM: BC010

Set measuring threaded inserts metric and whitworth

| Tech. Code | Set                                                                                                                                          | Thread    |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| D1350SET   | 0.4 + 0.5 - 0.6 + 0.9 - 1.0 + 1.75<br>2.0 + 3.0 - 3.5 + 5.0 - 5.5 + 7.0                                                                      | Metric    |
| D1355SET   | 60 + 48 TPI - 48 + 40 TPI - 40 + 32 TPI - 32 + 24 TPI<br>24 + 18 TPI - 18 + 14 TPI - 14 + 10 TPI<br>10 + 7 TPI - 7 + 4,5 TPI - 4,5 + 3,5 TPI | Whitworth |