



ITEM: D7290

Compact portable inspection camera to display the applications for a clear view in tight spots, not visible at glance.

3.5", wide angle LCD screen, to view, store and review pictures and footage.

Images can also be displayed directly on a TV screen, or stored and transferred to a PC using a USB cable.

SD mini card allows direct video recording or picture storage. An easy-to-transport standalone device, excellent for assessing damages, or simple diagnosis. Instant viewing of footage and image captures directly recorded on a high resolution TFT screen or external monitor. File transferred to computer by using a USB interface. Flexible 3m cable camera, 5.5mm diameter micro wide angle. Adjustable LED light for optimal view in all applications. In addition to the 45° and 90° mirrors supplied, the instrument can be easily equipped with several mirrors featuring different angles.

Cables of different sizes can also be supplied, as an optional item.

Equipment:

- Basic device with USB cable
- Probe diam. 5,5 with front cam
- AV2 cable for TV display
- 2GB SD card
- Spare battery
- Power adapter

Included

* Optional

* Optional

Tech. Code		Equipment	Probe m
D72906404801		Basic device with USB cable + Probe + AV2 cable + SD card + Battery + Power adapter	1
D72906404803			3

Performance:

- Semi-rigid cable, oil-proof and abrasion resistant
- N.4 enhanced illumination LEDs
- High speed video recording and image capture
- 2GB memory
- 300,000 pixel high definition resolution

Formats:

- Compression: MPEG4
- Image format: JPEG (640 x 480)
- Video format: ASF (320 x 240)
- Operating temperature: -10° - +70° C
- Dimensions: L94 x W78 x H10mm

VIDEOENDOSCOPES PROBES



ITEM: D7295

Tech. Code		Description
D7295CAVO1		Probe 1 m
D7295CAVO3		Probe 3 m