

KERFOLG® JOBBER DRILLS

DRILL DIN 338

A1120	Tech. Code		D mm	I mm	L mm		A1120	Tech. Code		D mm	I mm	L mm				
HEX N/R	A112010,5		10.50	87	133	5	HEX N/R	A112012,9		12.90	101	151	5			
	A112010,6		10.60					A112013		13.00						
	A112010,7		10.70	94	142			A112013,25		13.25	108	160	1			
	A112010,75		10.75					A112013,5		13.50						
	A112010,8		10.80					A112013,75		13.75						
	A112010,9		10.90					A112014		14.00						
	A112011		11.00					A112014,25		14.25	114	169				
	A112011,1		11.10					A112014,5		14.50						
	A112011,2		11.20					A112014,75		14.75						
	A112011,25		11.25					A112015		15.00						
	A112011,3		11.30					A112015,25		15.25	120	178				
	A112011,4		11.40					A112015,5		15.50						
	A112011,5		11.50					A112015,75		15.75						
	A112011,6		11.60					A112016		16.00	125	184				
	A112011,7		11.70					A112016,25		16.25						
	A112011,75		11.75					A112016,5		16.50						
	A112011,8		11.80					A112016,75		16.75						
	A112011,9		11.90	101	151			A112017		17.00	130	191				
	A112012		12.00					A112017,25		17.25						
	A112012,1		12.10					A112017,5		17.50						
	A112012,2		12.20					A112017,75		17.75						
	A112012,25		12.25					A112018		18.00	135	198				
	A112012,3		12.30					A112018,25		18.25						
	A112012,4		12.40					A112018,5		18.50						
	A112012,5		12.50					A112018,75		18.75						
	A112012,6		12.60					A112019		19.00	140	205				
	A112012,7		12.70					A112019,25		19.25						
	A112012,75		12.75					A112019,5		19.50						
	A112012,8		12.80					A112020		20.00						

KERFOLG® JOBBER DRILLS



ALU

ITEM: A1125

Geometry Special self-centering geometry, reduced cutting force

Point angle 130°

Surface treatment WIND Z

Application Carbon steel up to 850 N/mm², cast iron and aluminum alloys.
Low friction coefficient and great corrosion resistance.



< 500	< 850	< 1200	< 600	< 850	Duplex	< 200	< 300	< 10% Si	> 10% Si	Brass Copper	Bronze >700	Ti6Al4V	HTA	< 45	< 60
●	●		○			●	●	●	●						

DRILL DIN 338

A1125	Tech. Code		D mm	I mm	L mm	
HEX VWR	A112503		3,00	33	61	10
	A112503,3		3,30	36	65	
	A112503,5		3,50	39	70	
	A112504		4,00	43	75	
	A112504,2		4,20			
	A112504,5		4,50	47	80	
	A112505		5,00	52	86	
	A112505,5		5,50	57	93	
	A112506		6,00			
	A112506,5		6,50	63	101	
	A112506,8		6,80	69	109	
	A112507		7,00			
	A112507,5		7,50			

A1125	Tech. Code		D mm	I mm	L mm	
HEX VWR	A112508		8,00	75	117	10
	A112508,5		8,50			
	A112509		9,00	81	125	5
	A112509,5		9,50			
	A112510		10,00	87	133	
	A112510,2		10,20			
	A112510,5		10,50			
	A112511		11,00	94	142	
	A112511,5		11,50			
	A112512		12,00	101	151	
	A112512,5		12,50			
	A112513		13,00			