

## ALGRA DRIVEN TOOL HOLDERS KIT BMT 65

ITEM: C5510

For lathes: **DOOSAN**: Puma 2100/2600 (M,LM,MS,LMS), Puma 300 (M,MS,MB,MC), Puma 3100(M,LM,LY,XLM,XLY,ULM,ULY), Puma MX2000/2500, Puma MX2600 (T,ST), Puma TT2500 (MS/SY), Puma TX200 (M,Y,YY), Puma V400 (M), Puma VT450 (M,2SP); **GOODWAY**: GLS-2800, 3300, GS-2000, 2800, GLS-2800, 3300, GMS-2000 ST, GMT-2000, GTX/GTZ-2000, 2600; **HYUNDAI WIA**: L300 MA/MC/LMA/LMC/MSA/MS/LMSA, LM2000, 2500TTM/TTMS/TTSY, L2000, 2100, 2600, 3000, SKT200, 250 TTSY, SKT250, 300M/MS; **HARDINGE**: GS-65; **HWACHEON**: Cutex-240/Hi-TECH200/T2-Series, Hi-Tech 200,230,300,400,450MC/SMC/YMC/YSMC, VT-450, T2-Series MC/SMC/YMC/YSMC; **SAMSUNG**: PL 20/25/35M, PL 2000/2500M, SL 25, 35, 2500M/SY, 3500Y; **VICTOR**: Vturn-A26 CM, SCM, YCM, YSCM.

1

2

3

| Tech. Code     | Model            | Description                                                                           | Figure |
|----------------|------------------|---------------------------------------------------------------------------------------|--------|
| C5510RAPS32    | RAPS 32 121UT65  | Driven tool holder, axial 0°, collet ER32, external coolant, 6000 rpm; i=1:1          | 1      |
| C5510RRPPS3272 | RRPPS 32 121UT65 | Driven tool holder, radial 90°, collet ER32, H=72, external coolant, 6000 rpm; i=1:1  | 2      |
| C5510RRPPS3210 | RRPPS 32 321UT65 | Driven tool holder, radial 90°, collet ER32, H=100, external coolant, 6000 rpm; i=1:1 |        |
| C5510ROPPS25   | ROPPS 25 121UT65 | Driven tool holder orientable ± 90°, collet ER25, external coolant, 6000 rpm, i=1:1   | 3      |

## ALGRA STATIC TOOL HOLDERS BMT65

ITEM: C5512

For lathes: **DOOSAN**: Puma 2100/2600 (M,LM,MS,LMS), Puma 300 (M,MS,MB,MC), Puma 3100(M,LM,LY,XLM,XLY,ULM,ULY), Puma MX2000/2500, Puma MX2600 (T,ST), Puma TT2500 (MS/SY), Puma TX200 (M,Y,YY), Puma V400 (M), Puma VT450 (M,2SP); **GOODWAY**: GLS-2800, 3300, GS-2000, 2800, GLS-2800, 3300, GMS-2000 ST, GMT-2000, GTX/GTZ-2000, 2600; **HYUNDAI WIA**: L300 MA/MC/LMA/LMC/MSA/MS/LMSA, LM2000, 2500TTM/TTMS/TTSY, L2000, 2100, 2600, 3000, SKT200, 250 TTSY, SKT250, 300M/MS; **HARDINGE**: GS-65; **HWACHEON**: Cutex-240/Hi-TECH200/T2-Series, Hi-Tech 200,230,300,400,450MC/SMC/YMC/YSMC, VT-450, T2-Series MC/SMC/YMC/YSMC; **SAMSUNG**: PL 20/25/35M, PL 2000/2500M, SL 25, 35, 2500M/SY, 3500Y; **VICTOR**: Vturn-A26 CM, SCM, YCM, YSCM.

1

2

| Tech. Code     | MODEL            | Description                                                               | Figure |
|----------------|------------------|---------------------------------------------------------------------------|--------|
| C5512E10U25    | E10/U 25 T65X80  | Static tool holder axial Q=25, external coolant                           | 1      |
| C5512E10B4072  | E10/B 40 T65X72  | Static tool holder for boring bars, D=40, H=72, internal/external         | 2      |
| C5512E10B5072  | E10/B 50 T65X72  | Static tool holder for boring bars, D=50, H=72, internal/external coolant |        |
| C5512E10B40100 | E10/B 40 T65X100 | Static tool holder for boring bars D=40, H=100, internal/external coolant |        |