

ALGRA DRIVEN TOOL HOLDERS NL

ITEM: C5525

For lathes: **DMG MORI** NL / NLX 1500 - 12 station; NL / NLX 2000 - 12 station; NL / NLX 2500 - 12 station; NL / NLX 3000 - 12 station; NLX 4000; NT 4000 / 4200 / 4250 / 4300 / 5000 / 5400; NZL 2000 / 2500; NZX 2500 - 12 station.

1

2

3



Tech. Code	MODEL	Description	Figure
C5525RAPPH32	RAPPH 32 221UNL	Driven tool holder axial 0°, collet ER32, external coolant, 10000 rpm; i=1:1	1
C5525RAPPH40	RAPPH 40 121UNL	Driven tool holder axial 0°, collet ER40 external coolant, 10000 rpm; i=1:1	
C5525RRPPH32	RRPPH 32 121UNL	Driven tool holder radial 90°, collet ER32, external coolant, 10000 rpm; i=1:1	2
C5525RRPPH40	RRPPH 40 121UNL	Driven tool holder radial 90°, collet ER40, external coolant, 10000 rpm; i=1:1	
C5525ROPPh25	ROPPh 25 121UNL	Driven tool holder orientable $\pm 90^\circ$, collet ER25, external coolant, 10000 rpm, i=1:1	3

ALGRA STATIC TOOL HOLDERS NL

ITEM: C5527

For lathes: **DMG MORI** NL / NLX 1500 - 12 station; NL / NLX 2000 - 12 station; NL / NLX 2500 - 12 station; NL / NLX 3000 - 12 station; NLX 4000; NT 4000 / 4200 / 4250 / 4300 / 5000 / 5400; NZL 2000 / 2500; NZX 2500 - 12 station

1

2

3



Tech. Code	MODEL	Description	Figure
C5527E10US25	E10/US 25 NLX70	Static tool holder axial, Q=25, external coolant DMG MORI T00186	1
C5527E10BS40	E10/BS 40 NLX80	Static tool holder for boring bars, D=40, H=80 mm., external/internal coolant, DMG MORI T10097 -T13128	2
C5527E10BD32	E10/BD 32 NLX80/125	Static tool holders for boring bars, D=32, H=80/125 mm., external/internal coolant, DMG MORI T10096	3