

INTERMEDIATE PUSH-TO-CONNECT-FITTINGS

ITEM: 50230

Nickel-plated brass body. Pipe release pusher in acetalic resin. Clamping washer in AISI 304. NBR seals.
Working pressure -0.99 Bar min/20 Bar max.

Tech. Code		L552504	L552506	L552508	L552510	L552512
Pipe	mm	4	6	8	10	12
L1	mm	34	42	45	53	61
L2	mm	17	21	22.5	26.5	30.5
CH	mm	9	11	13	16	19
D	mm	10	12.5	14	17	21.5
		10				

INTERMEDIATE PUSH-TO-CONNECT-FITTINGS

ITEM: 55230

Technopolymer body. Pipe release pusher in acetalic resin ISOFORM. Nickel-plated brass capsule.
Clamping washer in AISI 304. NBR seals. Working pressure -0.99 Bar min/20 Bar max.

Tech. Code		L562504	L562506	L562508	L562510	L562512
Pipe	mm	4	6	8	10	12
L1	mm	33	41	44	53	61.5
L2	mm	16.5	20.5	22	26.5	30
CH	mm	9	11	13	16	19
D	mm	10	12	14	17	20
		10				

ORIENTING FLOW REGULATORS FOR CYLINDERS WITH TAPER THREAD - SHORT

ITEM: 50901

Screwdriver adjustment. Nickel-plated brass body. Pipe release pusher in acetalic resin.
Clamping washer in AISI 304. NBR seals. Working pressure 1 Bar min/20 Bar max.
Adjustment with screwdriver.

Tech. Code		L55300418	L553004M5	L55300614	L55300618	L55300814	L55300818
Pipe	mm	4		6		8	
A		1/8"	M5	1/4"	1/8"	1/4"	1/8"
B	mm	5.5	4	7	5.5	7	5.5
L1	mm	21	19	25	22.5	26	24
L2	mm	31	29.5	36.5	31	36.5	31
CH	mm	14	8	17	14	17	14
D	mm	10		12.5		14	
		10					

Please note: Short tapered thread allows coupling with different standard threads both cylindrical and conical, as BSP ISO 228 - ISO 7 BSPP/BSPT

POLYAMIDE PLUGS

ITEM: 8610

Polyamide plugs for tubes ideal for all types of use.

Tech. Code		L557004	L557006	L557008	L557010	L557012
Pipe	mm	4	6	8	10	12
L	mm	23.5	24.5	26	28.5	
		10				