

CRIMPING PLIERS FOR END SLEEVES 97 53 04

ITEM: 97 53 04

Crimping pliers for end sleeves DIN 46228 (part 1+4), automatic adaptation to the size of the end sleeves, quality of constant crimping with force stop device (self releasing mechanism) Increased clamping force from the articulated lever transmission. Chrome-vanadium oil-hardened tempered steel, handles coated in bi-component material.

Usage:

- ▣ Square pressing section of the end sleeves up to 16 mm²
- ▣ Square section pressing for optimal surfaces regardless of the positioning of the connection
- ▣ Pressing of all twin end sleeves up to 2 x 6 mm² o 2 x AWG 8

Tech. Code		Section mm ²	AWG	Length mm
F1035180		0,08 - 10 + 16	28 - 5	180

CRIMPING PLIERS FOR END SLEEVES 97 53 14

ITEM: 97 53 14

Crimping pliers for end sleeves DIN 46228 (part 1+4), automatic adaptation to the size of the end sleeves, quality of constant crimping with force stop device (self releasing mechanism) Increased clamping force from the articulated lever transmission. Chrome-vanadium oil-hardened tempered steel, handles coated in bi-component material.

Usage:

- ▣ Pressing with hexagonal section of end sleeves up to 10 mm²
- ▣ Hexagonal section pressing for difficult to access areas
- ▣ Pressing of all twin end sleeves up to 2 x 4 mm² o 2 x AWG 10

Tech. Code		Section mm ²	AWG	Length mm
F1036180		0,08 - 10	28 - 7	180

CRIMPING PILERS FOR END SLEEVES 97 53 18

ITEM: 97 53 18

Crimping pliers for end sleeves Din 46228 (part 1 + 4), Square crimping profile, 360° rotating crimp matrix with 8 trip positions, automatic adaptation to the desired dimensions of the sleeves. Tightening of Twin sleeve terminals up to 2x6 mm² . Constant crimping quality with a forced stop device (self releasing mechanism). Tempered and oil-hardened vanadium chrome steel, handles coated in two-component material.

Tech. Code		Section mm ²	AWG	Length mm
F1038200		0,14 - 16	26 - 5	200

CRIMPING PLIERS FOR END SLEEVES (FERRULES)

ITEM: 97 61 145 A

High resistant steel pliers for tightening socket terminals compliant with DIN 46228 (part 1+4) from 0,25 to 2,5 mm², tightening with trapezoidal profiles for a strong joint between conductor and terminal. Chrome-vanadium steel, forged oil-hardened resin coated handles.

Usage:

- ▣ For end sleeves (ferrules)

Tech. Code		Section mm ²	AWG	Length mm
F1040145		0,25 - 2,5	23 - 13	145

ITEM: 97 62 145 A

High resistant steel pliers for tightening socket terminals compliant with DIN 46228 (part 1+4) with nominal section from 0,25 to 2,5 mm², Tightening with trapezoidal profiles for a strong joint between conductor and terminal.

Chrome-vanadium steel, forged and oil-hardened, handles coated in bi-component material.

Usage:

- ▣ For end sleeves (ferrules)

Tech. Code		Section mm ²	AWG	Length mm
F1041145		0,25 - 2,5	23 - 13	145