END CUTTING NIPPERS FOR MECHANICS

ITEM: 68 01 200
STANDARD DIN ISO 5748

Front cutting nippers for metal wire of low and high resistance, also used to tie metal wires.
High performance chrome-vanadium steel, forged, oil-hardened, handles coated in resin.

Tech. Code		Length mm	High resistance wire ø max mm
F1795160		160	2,3
F1795200		200	2,8

ITEM: 61 02 200
Bonderized black pliers, clean head, bi-component coated taper-shaped handles. 64 HRC oil-hardened, vanadium, steel cutting edges

Tech. Code		Length mm	Cutting force 2300 N/mm² Ø max mm
F1798200		200	3

DIAGONAL CUTTING NIPPERS FOR PLASTIC MATERIALS

ITEM: 72 01 140/160/180
STANDARD DIN ISO 5743

Diagonal cutting nippers rectified cutting edges for sharp cuts without smearing of synthetic resins, with return spring.
Chrome-vanadium steel, forged, oil.hardened, handles coated wtih synthetic resin.

Tech. Code		Length mm
F1758140		140
F1758160		160
F1758180		180

INCLINED 45° CUTTING NIPPERS FOR PLASTIC MATERIALS

ITEM: 72 11 160
STANDARD DIN ISO 5743

45° Inclined cutting nippers with rectified cutting edges for sharp cutting without smearing synthetic resins, with return spring.
Chrome-vanadium steel forged, hardened, handles coated with synthetic resin.

Tech. Code		Length mm
F1760160		160

INCLINED 85° CUTTING NIPPERS FOR PLASTIC MATERIALS

ITEM: 72 21 160
STANDARD DIN ISO 5743

85° Inclined cutting nippers with rectified cutting edges for sharp cutting without smearing synthetic resins, with return spring.
Chrome-vanadium steel forged, hardened, handles coated with synthetic resin.

Tech. Code		Length mm
F1761160		160

CUTTING NIPPERS FOR ELECTRONICS AND FINE MECHANICS

ITEM: 77 02 115
STANDARD DIN ISO 9654

Side cutters suitable for precise cutting in electronics and fine mechanics, pass-through hinge and low friction and double spring for a soft and uniform opening/closing. Special steel for hardened, forged, oil-hardened tools, further Induction cutting edges with hardness approx. 60 HRC, handles coated in bi-component material.
Specific:
Round head model with semi-sharp edge.

Tech. Code		Length mm	High resistance wire Ø max mm
F1608115		115	0,6