

BATTERY RIVETERS

ITEM: M12 BPRT-201X

M12 BPRT-201X cordless riveting machine applies up to 325 4.8 mm stainless steel rivets with a single charge of a 2.0 Ah battery. Suitable for the application of rivets in aluminum, stainless steel and copper, with a diameter of Ø 2.4 mm up to a solid piece of Ø 4.8 mm. Stroke length of 20 mm. Clamps accessible without the use of tools. Possibility of storing the nozzles in the practical compartment placed on the tool. Works with all Milwaukee® M12™ batteries.

Tech. Code		F834012
Battery capacity	Ah	2
Blade stroke	mm	20,32
Ø jaw max.	mm	2,4 - 4,8
Traction force	N	9000
Weight with battery	Kg	2,1
Battery charging time	min	40
Battery type		Li-Ion
Voltage	V	12

Supplied with:
- 1 battery 12V da 2,0 Ah
- 1 battery charger
- carrying case

ON-LINE
MANUAL

PNEUMATIC RIVETERS FOR BLIND RIVETS

ITEM: RAC 83/95

Cast aluminum body, steel operating parts. Supplied complete with four nozzles.

Tech. Code		Rivets ø mm	Weight g
F8350RP/1		2,4 + 4,8 *	1500

* 4,8 ø only made from aluminium

ITEM: RAC 83 AX

Model with rivet retention and sliced nail recovery. Cast aluminum body, steel operating parts, supplied complete with four nozzles.

Tech. Code		Rivets ø mm	Weight g
F8360RP/2		2,4 + 4,8 *	1500

* 4,8 ø only made from aluminium

OLEO-PNEUMATIC RIVETERS FOR BLIND RIVETS

ITEM: RAC 181

Model with rivet retention and sliced nail recovery. Cast aluminium body, steel operating parts, supplied complete with six nozzles.

Tech. Code		Rivets ø mm	Weight g
F8380ROP/1		2,4 - 6 *	1600

* 6 ø only made from aluminium