

FLOOR SCALES



ITEM: BFB 1T - 4SNM

Ideal for weighing cases, boxes, small-sized pallets, painted milled steel non-skid platform, level and adjustable feet, large back lit LCD display, 52 mm digits, the indicator can be placed away from the base by using its 5m cable complete with wall stand, auto power off, load unaltered for three minutes, function can be disabled. 230V/50 Hz electric power supply.

Functions:

- ON/OFF: switch on and shutdown
- HOLD: allows for a stable weighing value even in presence of scale movement, holds the displayed weight value until Hold button is pressed again
- UNIT: unit of measurement conversion
- TARE: tare zero setting

Tech. Code	Description	Max capacity Kg	Dimension mm
D86901500	Platform	1500	1000x1000x85
D8690AR	Ramp up	-	1000x760x85
D8690AS	Stand		750 h

DIGITAL MULTIMETERS

ITEM: D9111

Professional all-purpose multimeter able to perform many measurements that are not possible with traditional instruments. CE marked, compliant with standards IEC EN 61010-1 CAT. III 1000V - CAT. IV 600V. Backlit LCD display, light shows which connections to use.

Auto power off after 15 min.

Power supply: 1 x 9V battery (not included).

Tech. Code	D91111	
Tension (AC/DC)	V	400m, 4, 40, 100, 250
Current (AC/DC)	A	400μ, 4m, 40m, 400m, 10
Frequency	Hz	5, 50, 500, 5k, 50k, 500k, 10M
Continuity	Ω	<50
Resistance	Ω	400, 4k, 40k, 400k, 4M, 40M
Brightness	Lux	4000 - 40000
Capacity	F	50n, 500n, 5μ, 50μ, 100μ
Noise level	dB	35 - 100
RH Humidity		33 - 99
Temperature	°C	-20 +1300 (Thermocouple)
Temperature	°C	-20 +40 (Internal sensor)

Tech. Code	D99159V	
Model	Battery 9V Transistor	
	1	

DIGITAL AMPEROMETRIC PLIERS

ITEM: D9216

Amperometric pliers/Multimeter, allow to perform current measurements (up to 1000A) without disconnecting the user CE, CAT. III 600V. 16mm LCD display with back-lightening illuminated pliers. Supplied with custody case. Auto-off function after 30 min. Power supply 3 batteries x 1,5V AAA (not included).

Tech. Code	D921601	
Tension (DC)	V	4V - 40V - 400V - 600V - 1000V
Tension (AC)	V	4V - 40V - 400V - 600V - 700V
Current (ac/dc)	Ah	400A - 600A - 1000A
Duty cycle		0,1 - 99,9%
Resistance	Ω	400 - 4K - 40K - 400K - 4M - 40M

Tech. Code	D99251,5V	
Model	- AAA-type 1.5 battery	