

WODEX 6 UNIVERSAL COMBINATION PLIERS

ITEM: WX3050
STANDARD DIN/ISO 5746



PREMIUM QUALITY combination universal pliers made of chromium-molybdenum steel, with satin finish, cutting of high resistance precise Induction hardened.
Hardness: Handles 43-48 HRC, cutting nipper 58-60 HRC.
Hypoallergenic **ERGOFORM** grip handles, anti-slip, soft and comfortable, in **SANTOPRENE®** which guarantees maximum resistance for fast and precise work.
Compliant with RoHS e REACH directives.

Tech. Code	Length mm	Hardness cutting HRC
F0090160	160	58 - 60
F0090180	180	
F0090200	200	

UNIVERSAL COMBINATION PLIERS

ITEM: F0101
STANDARD DIN/ISO 5746

Universal combination pliers made of chrome-vanadium steel, with satin finish and induction hardened cutting hedges. Hypoallergenic ergonomic grips in TPR soft-Touch.

Tech. Code	Length mm	Steel wire Ø max mm
F0101180	180	1,8
F0101200	200	2,1

WODEX 6 UNIVERSAL COMBINATION PLIERS VDE INSULATED 1000 VOLTS IN SET

ITEM: WX3752/S3
Set of universal combination pliers **PREMIUM QUALITY** isolated up to 1000V
DIN EN 60900 / VDE 0682-201, hypoallergenic **ERGOFORM** handles, non-slip, soft and comfortable.
Compliant with RoHS and REACH



Composition: **WX3060** Universale pliers VDE 180 mm
WX3210 Half round bent nose pliers VDE 200 mm
WX3610 Diagonal cutting nippers VDE 160 mm

Tech. Code	Pieces
F010203	3

Assortment in box

ERGOFORM UNIVERSAL COMBINATION PLIERS STRONG TYPE

ITEM: 02 01 180 - 02 01 200
STANDARD DIN/ISO 5746

Special steel pliers for quenched tools, forged and oil-hardened high tempered Induction cutting with hardness approx. 63 HRC, for high resistant metallic wire and piano wire, handles coated in synthetic resin.

Tech. Code	Length mm	Piano wire Ø max mm
F0140180	180	2,0
F0140200	200	2,2

ITEM: 02 05 180/200/225
STANDARD DIN/ISO 5746

Special steel pliers for quenched tools, forged and oil-hardened high tempered Induction cutting with hardness approx. 63 HRC, for high resistant metallic wire and piano wire, handles coated in bi-component material.

Tech. Code	Length mm	Piano wire ø max mm
F0142180	180	2
F0142200	200	2,2
F0142225	225	2,5