



I25.K



Forma KE




Forma KU

PFERD - Oxido Al Rosa - AR O 5V - DIN 69170


D x L	E	Grão	CÓDIGO	Grão	CÓDIGO
10 x 10	3	46	KE 10 10-3		
	6	80	KE 10 10-6		
10 x 25	6	80	KE 10 25-6		
13 x 13	6	80	KE 13 13-6		
16 x 16	6	60	KE 16 16-6	30	KE 16 16-6G
16 x 45	6	80	KE 16 45-6	46	KE 16 45-6G
20 x 20	6	60	KE 20 20-6	30	KE 20 20-6G
20 x 32	6	60	KE 20 32-6	30	KE 20 32-6G
20 x 40	6	60	KE 20 40-6	30	KE 20 40-6G
25 x 25	6	60	KE 25 25-6	30	KE 25 25-6G
25 x 45	6	60	KE 25 45-6	30	KE 25 45-6G
32 x 32	6	46	KE 32 32-6		

D	E	Grão	CÓDIGO	Grão	CÓDIGO
3	3	100	KU 03-3		
	6	100	KU 03-6		
5	3	100	KU 05-3		
	6	100	KU 05-6		
8	3	80	KU 08-3		
	6	80	KU 08-6	46	KU 08-6G
10	3	80	KU 10-3		
	6	80	KU 10-6	46	KU 10-6G
13	3	80	KU 13-3		
	6	80	KU 13-6	46	KU 13-6G
16	6	60	KU 16-6	30	KU 16-6G
20	6	60	KU 20-6	30	KU 20-6G
25	6	60	KU 25-6	30	KU 25-6G
32	6	46	KU 32-6	24	KU 32-6G

I25.S



Forma SP



Forma WR

PFERD - Oxido Al Rosa - AR O 5V - DIN 69170

D x L	E	Grão	CÓDIGO	Grão	CÓDIGO
3 x 6	3	100	SP 03 06-3		
	6	100	SP 03 06-6		
5 x 10	3	100	SP 05 10-3		
	6	100	SP 05 10-6		
8 x 16	3	80	SP 08 16-3		
	6	80	SP 08 16-6	46	SP 08 16-6G
13 x 20	6	80	SP 13 20-6	46	SP 13 20-6G
20 x 32	6	60	SP 20 32-6	30	SP 20 32-6G
20 x 50	6	30	SP 20 50-6		
25 x 40	6	30	SP 25 40-6		

D x L	E	Grão	CÓDIGO	Grão	CÓDIGO
3 x 6	3	100	WR 03 06-3		
	6	100	WR 03 06-6		
5 x 10	3	100	WR 05 10-3		
	6	100	WR 05 10-6		
8 x 16	6	80	WR 08 16-6	46	WR 08 16-6G
13 x 20	6	80	WR 13 20-6	46	WR 13 20-6G
20 x 25	6	60	WR 20 25-6	30	WR 20 25-6G

Obs : Para pedido defina I25.CÓDIGO.
 Velocidade de trabalho 15-40 m/s.
 Equivalente a **PFERD** tipo KE, KU, SP e WR, respectivamente.

Medidas em milímetros